



Description	GFCI, In-Line Style with Cord
Rated Current	20 amps
Rated Supply Voltage	120 Volts
Frequency	50/60 Hz
Polarity	2 Pole 3 Wire
Tripping Current	4-6 mA
Maximum Tripping Time	25 ms
Ambient Temperature Range	-35C to 66C
Reset Type upon Power Loss	Automatic (also known as Passive or Latching)
Color	Black
Design	UL Standard 943 Class A UL Listed, CSA Certified Rainproof Design
Plug	IEC 60309 IP44 4H, Straight
Cordage	12/3 awg SJTW, Black
Receptacle (Connector)	IEC 60309 IP44 4H, Straight
Function	Test and Reset Buttons not to be used as ON/OFF switch

ALL DIMENSIONS ARE IN MILLIMETERS

**WORLD CORD SETS, INC.**

TEL (860)763-2100  
FAX (860)763-1183



www.WorldCordSets.com  
sales@WorldCordSets.com

TITLE

GFCI CORD SET, IN-LINE STYLE

THIS DOCUMENT AND THE INFORMATION CONTAINED HEREIN ARE THE PROPRIETARY CONFIDENTIAL PROPERTY OF WORLD CORD SETS.  
NO USE OR REPRODUCTION IN PART OR WHOLE MAY BE MADE WITHOUT WRITTEN PERMISSION FROM WORLD CORD SETS.

SCALE  
NONE

DATE  
12-3-2007

PART NO.  
LAB7-N24N-XXXX

REV  
—