


IEC 60309 IP44
4H Plug



| | |
|----------------------------|---|
| Description | GFCI, In-Line Style with Cord |
| Rated Current | 20 amps |
| Rated Supply Voltage | 120 Volts |
| Frequency | 50/60 Hz |
| Polarity | 2 Pole 3 Wire |
| Tripping Current | 4-6 mA |
| Maximum Tripping Time | 25 ms |
| Ambient Temperature Range | -35C to 66C |
| Reset Type upon Power Loss | Automatic (also known as Passive or Latching) |
| Color | Black |
| Design | UL Standard 943 Class A UL Listed, CSA Certified Rainproof Design |
| Plug | IEC 60309 IP44 4H, Straight |
| Cordage | 12/3 awg SJTW, Black |
| Receptacle (Connector) | None, 2" ROJ and Strip All 1/4" |
| Function | Test and Reset Buttons not to be used as ON/OFF switch |

ALL DIMENSIONS ARE IN MILLIMETERS

WORLD CORD SETS, INC.

TEL (860)763-2100
FAX (860)763-1183



www.WorldCordSets.com
sales@WorldCordSets.com

TITLE

GFCI CORD SET, IN-LINE STYLE

THIS DOCUMENT AND THE INFORMATION CONTAINED HEREIN ARE THE PROPRIETARY CONFIDENTIAL PROPERTY OF WORLD CORD SETS.
NO USE OR REPRODUCTION IN PART OR WHOLE MAY BE MADE WITHOUT WRITTEN PERMISSION FROM WORLD CORD SETS.

SCALE
NONE

DATE
12-3-2007

PART NO.
LAB7-N24W-XXXX

REV
—