



|                            |   |
|----------------------------|---|
| Description                | GFCI, Plug-Head Style with Cord   |
| Plug Configuration         | Nema 5-15p  |
| Rated Current              | 10 amps   |
| Rated Voltage              | 125 Volts   |
| Frequency                  | 50/60 Hz  |
| Polarity                   | 2 Pole 3 Wire   |
| Tripping Current           | 4-6 mA  |
| Maximum Tripping Time      | 25 ms   |
| Ambient Temperature Range  | -35C to 66C   |
| Reset Type upon Power Loss | Automatic (also known as Passive or Latching)   |
| Color                      | Black   |
| Design                     | UL Standard 943 Class A with open neutral protection<br>UL Recognized<br>Rainproof Design |
| Cordage                    | 18/3 SJTW, Black  |
| Receptacle (Connector)     | IEC 60320 C-15A, Straight, Molded or Mounted  |
| RoHS                       | RoHS compliant model is available   |
| Function                   | Test and Reset Buttons not to be used as ON/OFF switch                                    |

ALL DIMENSIONS ARE IN MILLIMETERS

|                               |   |                         |     |
|-------------------------------|---|-------------------------|-----|
| <b>WORLD CORD SETS, INC.</b>  |   |                         |     |
| TEL (860)763-2100             |  | www.WorldCordSets.com   |     |
| FAX (860)763-1183             |   | sales@WorldCordSets.com |     |
| TITLE                         |   |                         |     |
| GFCI CORDSET, PLUG-HEAD STYLE |   |                         |     |
| SCALE                         | DATE  | PART NO.                | REV |
| NONE                          | 12-3-2007   | PAB2-21C-0120           | -   |

THIS DOCUMENT AND THE INFORMATION CONTAINED HEREIN ARE THE PROPRIETARY CONFIDENTIAL PROPERTY OF WORLD CORD SETS. NO USE OR REPRODUCTION IN PART OR WHOLE MAY BE MADE WITHOUT WRITTEN PERMISSION FROM WORLD CORD SETS.