



Description	GFCI, Plug-Head Style with Cord
Plug Configuration	Nema 5-15p
Rated Current	15 amps
Rated Voltage	125 Volts
Frequency	50/60 Hz
Polarity	2 Pole 3 Wire
Tripping Current	4-6 mA
Maximum Tripping Time	25 ms
Ambient Temperature Range	-35C to 66C
Reset Type upon Power Loss	Automatic (also known as Passive or Latching)
Color	Black
Design	UL Standard 943 Class A with open neutral protection c-ETL-us Listed (INTERTEK) Rainproof Design
Cordage	14/3 SJT
Receptacle (Connector)	IEC 60320 C-13, Straight, Molded, Black
RoHS	RoHS compliant model is available
Function	Test and Reset Buttons not to be used as ON/OFF switch

ALL DIMENSIONS ARE IN MILLIMETERS

WORLD CORD SETS, INC.

TEL (860)763-2100
FAX (860)763-1183



www.WorldCordSets.com
sales@WorldCordSets.com

TITLE
GFCI CORD SET, PLUG-HEAD STYLE

THIS DOCUMENT AND THE INFORMATION CONTAINED HEREIN ARE THE PROPRIETARY CONFIDENTIAL PROPERTY OF WORLD CORD SETS. NO USE OR REPRODUCTION IN PART OR WHOLE MAY BE MADE WITHOUT WRITTEN PERMISSION FROM WORLD CORD SETS.

SCALE NONE	DATE 12-3-2007	PART NO. PAB4-13A-0036	REV A
---------------	-------------------	---------------------------	----------