



Description	RCD, Plug-Head Style with Cord
Plug Configuration	SCHUKO CEE 7/7
Rated Current	16 amps
Rated Voltage	220-240 Volts
Frequency	50 Hz
Polarity	2 Pole 3 Wire
Tripping Current	15 to 30 mA (maximum)
Maximum Tripping Time	30 ms
Ambient Temperature Range	-25C to 40C for RCD (+5C to 60C for cordage)
Reset Type upon Power Loss	Manual (also known as Active or non-Latching)
Color	Black
Design	GS Approval, CE, Tested by Intertek, Type A Protection grade for housing: IP54 Tested according to DIN VDE 0620-1:2005
Cordage	3x1.5 mm ² H05VV-F, Black Jacket
Receptacle (Connector)	IEC 60320 C-19
RoHS	RoHS compliant
Function	Test and Reset Buttons not to be used as ON/OFF switch

ALL DIMENSIONS ARE IN MILLIMETERS

WORLD CORD SETS, INC.

TEL (860)763-2100
FAX (860)763-1183



www.WorldCordSets.com
sales@WorldCordSets.com

TITLE			
RCD CORD SET, PLUG-HEAD STYLE			
SCALE	DATE	PART NO.	REV
NONE	12-3-2007	R1B2-23D-XXXX	A